

V700S

SLAM RTK





Full-Constellation Tracking: Strong Signal & High-Quality Data

- **Supports 1408 channels**
- **New GNSS SoC chip:** Low power consumption, extended battery life.
- **Advanced technology:** Advanced multi-frequency anti-interference and adaptive filtering technology ensures strong signal reception, high-quality data and excellent accuracy.



Innovative Industrial Design

- **Compact & lightweight** for easy handling.
- **Screw-lock mechanism** securely connects the device and battery handle, ensuring reliable and stable operation.

N:2542629.911

E:435687.323

H:2.645




Contactless Measurement

- Utilizing laser point cloud data and image data provides real-time acquisition of rich geospatial information efficiently and conveniently.
- This technology greatly expands the application scope of GNSS, allowing measurements in areas like under bridges, culverts, and enclosed spaces, ensuring efficient and safe operations.
- Leveraging Android's high-performance laser point cloud and image processing technology, users can simply take a photo to obtain coordinates of multiple points on the handheld software. With an accuracy of 5cm, it doubles working efficiency.



Unified Coordinate Framework

- RTK + SLAM Fusion: V700S delivers real-time centimeter-level positioning outdoors while automatically aligning point cloud data, ensuring unified coordinate output (BLH/NEH).
- Control-free scanning: V700S requires no control points, allowing users to scan freely without returning to previous locations - dramatically improving on-site efficiency.



Laser Reverse Positioning Technology: Precision Measurement without Signal

Hi-Target's innovative Laser Reverse Positioning Technology enables seamless cross-environment measurement. Outdoors, the high-precision RTK module delivers centimeter-level accuracy. In GNSS-denied areas like under bridges or eaves, the system automatically switches to laser-based positioning, ensuring uninterrupted data capture.





Real-time Volume Calculation

Through laser point cloud data, rich three-dimensional data of ground objects can be obtained in real time. By leveraging high-performance Android-based processing technology, quantitative results can be derived efficiently and conveniently.



8-INCH ROBUST TABLET



2.0GHz, 8 cores high-speed processor



6+128GB large memory



8200 mAh high capacity battery



Based on Android 10, more smooth operation



APPLICATIONS




Urban Renewal



Volume Measurement



Tunnel Surveying



Forestry Survey



Underground Pipelines




Architectural Survey

SOFTWARE

Hi-Survey Field Software

- High-performance laser point cloud & image processing engine for real-time solutions and visualization.
- Precision heat map display allows users to monitor accuracy in real time.
- Integrates industry-leading CAD & real-scene engines for an intuitive, visual measurement and layout experience.



Office Software for Post-processing

- Hi-LiDAR software refines real-time data, delivering point clouds with sub-2 cm thickness and <1 cm relative measurement precision.
- Automated excavation analysis: Calculates over/under-excavation for tunnel sections, enabling construction progress tracking and validation.
- Advanced section visualization & drafting: Supports horizontal/vertical section views, aiding in renovation planning for older buildings with precise architectural measurements.



AUTHORIZED DISTRIBUTION PARTNER

250120

Hi-Target Surveying Instrument Co. Ltd

ADD: Hi-Target Headquarters, No. 6, Hongchuang 2nd Street,
Nancun Town, Panyu District, 511442 Guangzhou, China

www.hi-target.com.cn +86-20-28688296 sales@hi-target.com.cn

TECHNICAL SPECIFICATIONS

GNSS Configuration	Channel	1408	
	GNSS Signal	GPS: L1C/A, L1C, L2P(Y), L2C, L5	
		BDS: B1I, B2I, B3I, B1C, B2a, B2b	
		GLONASS: L1, L2, L3	
		GALILEO: E1, E5a, E5b, E6	
		QZSS: L1, L2, L5, L6	
		NavIC: L5	
		SBAS: L1, L2, L5	
		PPP: B2b-PPP, E6-HAS	
	Output Format	ASCII: NMEA-0183, Binary	
Output Rate	1Hz~20Hz		
Static Data Format	GNS, Rinex		
Real Time Kinematic	RTCM2.X, RTCM3.X		
Network Mode	VRS, FKP, MAC, Support NTRIP protocol		
System Configuration	Operation System	Linux	
	Storage	Circulating 512GB ROM	
Accuracy and Reliability ^[1]	High-precision Static	H: 2.5 mm + 0.1 ppm RMS	V: 3.5 mm + 0.4 ppm RMS
	Static And Fast Static	H: 2.5 mm + 0.5ppm RMS	V: 5 mm + 0.5ppm RMS
	PPK	H: 8mm + 1ppm RMS	V: 15mm + 1ppm RMS
	PPP	H: 10cm	V: 20cm
	Code Differential Gnss Positioning	H: ±0.25m+1ppm RMS SBAS: 0.5m (H), 0.85m (V)	V: ±0.5m+1ppm RMS
	Real Time Kinematic (RTK)	H: 8mm+1ppm RMS Initialization time: Typically <10s	V: 15mm+1ppm RMS Initialization reliability: Typically > 99.9%
	Tilt Survey Performance ^[2]	8mm+0.3mm/°tilt	
	Ar Stakeout	Support	
	Image Measurement	A single photo can acquire multiple point coordinates with an accuracy of 5cm ^[3]	
	Real-time Accuracy Evaluation	Supports	
Camera	Pixel	3 professional HD front cameras, 1bottom camera	
	Function	Support AR stakeout, image measurement, working distance 2~15m	
Laser Scanner	Range	0.1~ 40m@10%, 0.1~ 70m@80%	
	Point Measurement Rate	200,000 pts/sec	
	Laser Product Classification	Class 1 eye safe	
	FOV	H: 360°	V: 59°
IMU	Update Rate	200Hz	
Communication	I/O Interface	USB type C port; SMA antenna port; Nano SIM card slot	
	Network	TDD-LTE, FDD-LTE, GSM	
	Wi-Fi	IEEE 802.11a/b/g/n/ac/ax, 2.4GHz/5GHz, Wi-Fi hotspot	
	Bluetooth	Bluetooth 5.2	
	Internal UHF Radio	Power: 0.5W/1W adjustable Frequence: 410MHz~470MHz Protocol: HI-TARGET, TRIMTALK450S, TRIMMARK III, SATEL-3AS, TRANSEOT, etc. Channel: 116 (16 scalable)	
Sensor	Electronic Bubble	Supports	
	Tilt Survey	Built-in high-precision IMU module	
Control Panel	Physical Button	Single button	
	Display	2.8 inch, 480×640 pixel touchable screen	
	Led Lights	Mode, accuracy, network	
Application	Advanced Function	NFC, WebUI, firmware upgrade via u-disk	
	Intelligence Application	Intelligent voice, self-check	
	Remote Service	Message push, online upgrade, remote control	
Physical	Power ^[4]	Lithium battery, portable charger	
		Operating time (built-in battery): RTK rover(UHF/Cellular): up to 4 hours SLAM mode: up to 2 hours	
		Operating time (external battery): RTK rover(UHF/Cellular): up to 10 hours SLAM mode: up to 5 hours USB 45W fast charging, fully charged in 2 hours	
	Size	Φ134.4mm×109.9mm	
Weight	1.68kg		
Environments	IP Rating	IP64	
	Humidity	100% non-condensing	
	Operation Temperature	-20 ℃~+55 ℃	
	Storage Temperature	-40 ℃~+70 ℃	

Note:
[1]The measurement accuracy, precision, reliability and initialization time depend on various factors, including tilt angle, number of satellites, geometric distribution, observation time, atmospheric conditions and multi-path validation, etc. The data are derived under normal conditions.
[2]Irregular operations such as rapid rotation and high-intensity vibration may affect the inertial navigation accuracy.
[3]The results are the accuracy obtained in laboratory scenarios, and some scenarios may have accuracy deviations.
[4]The battery operating time is related to the operating environment, operating temperature and battery life.
Descriptions and Specifications are subject to change without notice.