



# V600L

## LASER RTK



# Hi-Target V600L LASER RTK

Hi-Target next-generation Laser RTK that combines GNSS, IMU, dual-camera, and visible laser technologies for immersive, efficient, and precise fieldwork—especially in environments like under bridges, near fences, or across ditches.

With visualized laser targeting and non-contact measurement, it unlocks a new level of accessibility and safety in obstructed, complex, or semi-enclosed terrains.



## High-Precision Laser Surveying — Even Without GNSS

By fusing laser and visual technologies, our system delivers non-contact measurements with up to 2 cm accuracy within 10 m and laser ranging up to 45m<sup>①</sup>. Operate confidently in GNSS-denied environments such as under bridges, inside fenced zones, or across ditches, all from a safe and convenient distance.



## IMU You Can Trust — No Initialization Needed

With automotive-grade IMU, no initialization needed. Start measuring instantly with up to 40% better stability and accuracy, even on rugged terrain.



## Built-in LoRa Radio, Cross-Brand Compatibility

Integrated LoRa transceiver supports multiple protocols and brands, delivering over 15 km working range in typical environments.

Note:

① Maximum ranging distance tested under ideal conditions.

# Hi-Survey Software

## Survey Data Collection Software

Hi-Survey is an Android software that is designed for all types of land survey and road engineering projects in the field. It is compatible with Hi-Target professional controllers, Android phones, tablets and other third-party Android devices. It is a sleek and easy-to-use software that supports the operating of big data with built-in tools. With customized industrial application solutions, more possibilities are created for users.



### Visual Laser Targeting

Seamlessly integrates laser and imaging technologies displaying the laser spot directly on the screen for fast, intuitive aiming. No guesswork, no extra steps.



### Real-Scene CAD Stakeout

Combines a high-performance CAD engine with real-world imagery to deliver a visual stakeout experience. Stake with confidence and boost efficiency by up to 50%.



AUTHORIZED DISTRIBUTION PARTNER

25N105

### Hi-Target Surveying Instrument Co. Ltd

ADD: Hi-Target Headquarters, No. 6, Hongchuang 2nd Street,  
Nancun Town, Panyu District, 511442 Guangzhou, China  
[www.hi-target.com.cn](http://www.hi-target.com.cn) +86-20-28688296 [sales@hi-target.com.cn](mailto:sales@hi-target.com.cn)

## TECHNICAL SPECIFICATIONS

GNSS Signal <sup>[1]</sup>	Channel	1760	
	GPS	L1C/A, L1C, L2P(Y), L2C, L5	
	BDS	B1I, B2I, B3I, B1C, B2a, B2b	
	GLONASS	L1, L2, L3	
	GALILEO	E1, E5a, E5b, E6	
	QZSS	L1, L2, L5, L6*	
	NavIC	L5	
	SBAS	L1, L2, L5	
	PPP	B2b-PPP	
	High-Precision Static	H: 2.5 mm + 0.1 ppm RMS	V: 3.5 mm + 0.4 ppm RMS
	Static and Fast Static	H: 2.5 mm + 0.5 ppm RMS	V: 5 mm + 0.5 ppm RMS
	Post Processing	H: 3 mm + 1 ppm RMS	V: 5 mm + 1 ppm RMS
	Kinematic (PPK / Stop & Go)	Initialization time: 10 min for base and 5 min for rover	Initialization reliability: typically >99.9%
	PPP	H: 10 cm V: 20 cm	
Positioning Performance <sup>[2]</sup>	Code Differential HNGG	H: ±0.25 m+1 ppm RMS	V: ±0.5 m+1 ppm RMS SBAS: 0.5 m (H), 0.85 m (V)
	RTK(UHF)	H: 8 mm+1 ppm RMS Initialization time: typically < 10 s	V: 15 mm+1 ppm RMS Initialization reliability: typically > 99.9%
	RTK(Network)	H: 8 mm+0.5 ppm RMS Initialization time: typically < 10 s	V: 15 mm+0.5 ppm RMS Initialization reliability: typically > 99.9%
	Hi-Fix <sup>[3]</sup>	H: RTK+10 mm / minute RMS	V: RTK+20 mm / minute RMS
	Time to First Fix <sup>[4]</sup>	Cold start: < 45 s	Hot start: < 30 s
	Positioning Frequency	1 Hz, 5 Hz and 10 Hz	
	Tilt Survey Performance	200 Hz, auto calibration, additional horizontal pole-tilt uncertainty typically less than H: 8 mm+0.7 mm/°tilt (0~120°); V: 15 mm+0.7 mm/°tilt (0~120°)	
	Image Stakeout Accuracy	2 cm accuracy	
	Laser Measurement	2 cm accuracy within 10 m	
	Dimensions (W x H)	130.97 mm × 68.7 mm	
Physical	Weight	≤ 0.73 kg ( 1.61 lb )	
	Operation Temperature	-45 °C ~ +75 °C (-40°F ~ +167°F)	
	Storage Temperature	-55 °C ~ +85 °C (-67°F ~ +185°F)	
	Humidity	100% non-condensing	
	IP Rating	IP68 ( according to IEC 60529 )	
	Shock and Vibration	MIL-STD-810G, 514.6	
	Free Fall	Designed to survive a 2 m natural fall onto concrete	
Electrical	Internal Battery <sup>[5]</sup>	RTK rover(UHF/GSM): up to 20 h; UHF RTK Base: up to 13 h; GSM RTK Base: up to 17 h	
	External Power	using standard smartphone chargers or external power banks (Support 5V 2.8A Type-C USB external charging)	
Communication	I/O Interface	1 × USB type C port; 1 × SMA antenna port, 1 × Nano SIM card slot	
	Wi-Fi	Frequency 2.4 GHz, supports 802.11 a/b/g/n/ac/ax	
	Bluetooth	BT 5.2, 2.4 GHz	
	NFC	Near field communication for device touch pairing	
	Network Modem	TDD-LTE, FDD-LTE, GSM	
	Internal UHF Radio	Power: 1 W / 2 W adjustable	
		Frequency: 410 MHz~470 MHz	
		Protocol: LoRa, HI-TARGET, TRIMTALK450S, TRIMMARK III, SATEL-3AS, TRANSEOT, etc.	
		Working range: 15-20 km <sup>[6]</sup>	
Laser	Laser Performance	Channel: 116 (16 scalable)	
		Class 3R, Laser ranging up to 45m	
Camera	Front Camera	5MP, support image-assisted measurement and AR stakeout	
	Bottom Camera	2MP, support AR stakeout	
Control Panel	Physical Button	1	
	LED Lights	Satellite, signal, power	
System Configuration	Storage	64 GB ROM internal storage	
	Output Format	ASCII: NMEA-0183	
	Output Rate	1Hz~20Hz	
	Static Data Format	GNS, Rinex	
	Real Time Kinematic (RTK)	RTCM2.X, RTCM3.X, CMR	
	Network Mode	VRS, FKP, MAC, support NTRIP protocol	
	Accessory	Tripod stand, Tribrach with adaptor, GNSS pole, Pole catcher, Base extension pole, Connector for base, UHF antenna, Charger and adaptor	

Note:

[1]QZSS L6 can be provided by firmware upgrade.

[2]The measurement accuracy, precision, reliability and initialization time depend on various factors, including tilt angle, number of satellites, geometric distribution, observation time, atmospheric conditions and multi-path validation, etc. The data are derived under normal conditions.

[3]Accuracies are dependent on GNSS satellite availability. Hi-Fix Positioning ends after 5 minutes without differential data.Hi-Fix is not available in all regions, check with your local sales representative for more information.

[4]Irregular operations such as rapid rotation and high-intensity vibration may affect the inertial navigation accuracy.

[5]Rechargeable built-in 7.2V / 4900 mAh lithium battery; operating time varies with environment, temperature, and battery condition.

[6]This distance can be achieved when using a super base station.

\*Descriptions and Specifications are subject to change without notice